



Anybus X-gateway - Lonworks Slave - Lonworks Slave

The Anybus X-gateway allows you to seamlessly inter-connect/extend PLC control systems and their connected devices on a Lonworks network.

FAST COPYING OF I/O DATA

The X-gateways primary function is with the fast transfer of cyclic I/O data between the two PLC systems. This offloads your PLC from working with additional calculations. The gateway acts as a Slave and provides a simple network extension. The data transmission is completely transparent with a maximum data capacity of 512 bytes (256 LW variables) in each direction.

EASY CONFIGURATION - NO PROGRAMMING REQUIRED!

The connection between the two networks is quickly set up in the Anybus Configuration Manager software, included with the X-gateway. No programming skills are needed to set up the X-gateway. As factory default the X-gateways have a pre-defined I/O size of 20 bytes I/O.



Features and benefits

- Fast copying of cyclic I/O data between the two Lonworks networks (10-15 ms)
- Proven and tested with all PLC manufacturers
- Supports up to a maximum of 512 bytes (256 LW variables) of Input and Output data in each direction
- Optional control and status information added to the I/O data for diagnostic purposes
- Robust stand-alone housing for use in harsh industrial environments
- Global free technical support and consultancy

Lonworks Slave interface

Lonworks network variables and configuration is made via an included configuration tool

- Certified for Lonmark application layer guidelines V3.2
- Lonworks network variables and configuration of the gateway is made via the included configuration tool (network commissioning requires 3rd part tools)
- Lonworks FT-X1 Transceiver
- Up to 256 input + 256 output LonWorks Network Variables / Modbus Word Registers
- Support for up to 15 nodes
- Amount and type of network variables configurable, data linking between Lonworks variables (SNVT's) and Modbus Registers
- Lonworks baudrate 78 kbit/s
- 1x D-sub 9-pin male RS-232 configuration port
- 1x 5-pin, 5.08 Phoenix network connector

Lonworks Slave interface

Lonworks network variables and configuration is made via an included configuration tool

- Certified for Lonmark application layer guidelines V3.2
- Lonworks network variables and configuration of the gateway is made via the included configuration tool (network commissioning requires 3rd part tools)
- Lonworks FT-X1 Transceiver
- Up to 256 input + 256 output LonWorks Network Variables / Modbus Word Registers
- Support for up to 15 nodes
- Amount and type of network variables configurable, data linking between Lonworks variables (SNVT's) and Modbus Registers
- Lonworks baudrate 78 kbit/s
- 1x D-sub 9-pin male RS-232 configuration port
- 1x 5-pin, 5.08 Phoenix network connector

TECHNICAL SPECIFICATIONS

Dimensions (L•W•H)	114 x 44 x 127mm or 4,49 x 1,73 x 5,00"
Weight	400g or 0,880 lbs
Operating temperature	-25 to +65 °C or -13 to +149 °F
Storage temperature	-40 to +85 °C or -40 to +185 °F
Power supply	24 VDC +/- 20% via 2-pole 5.08 mm Phoenix pluggable screw connector
Current consumption	max. 400mA (Typical 200mA)
Enclosure material	Aluminium and plastic
Installation position	Vertical / Flat*
Galvanic isolation	YES, on both BUS/Ethernet side
Mechanical rating	IP20, NEMA rating 1
Mounting	DIN-rail (EN 50022 standard)
I/O configuration	via USB port with Anybus Configuration Manager software
Certifications	CE, CULUS, RoHS

File	Version	Size	Read online
------	---------	------	-------------

Ordering information

Order Code	AB7628
Included components	Gateway Quick start documentation USB configuration cable Resource CD with Lonworks configuration software Power supply not included Configuration software is available for download

3 year guarantee. For purchasing instructions and terms and conditions, see: [How to buy](#).

Copyright © 2020 HMS Industrial Networks - All rights reserved.